

**New
innovative
product**



chromodomi
paint & insulation

LIFE ACRYL



Elastic Fiber



**100% ACRYLIC
FIBER-REINFORCED ELASTOMERIC PAINT**



- ✓ **Top quality**
- ✓ **Great flexibility**
- ✓ **Excellent resistance to external weather conditions**

LIFE ACRYL

Elastic Fiber

GENERAL CHARACTERISTICS

Top quality, 100% acrylic fiber-reinforced elastomeric paint for exterior use. It has great flexibility, excellent resistance to external weather conditions and covers completely capillary and microcracks. Ideal for painting exterior walls, plaster, concrete, cement etc.

APPLICATION

Stir well before use the product and do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. To ensure proper adhesion of the paint have to the surface be cleaned from dust, grease, oil, peeling old paint, rust, mold or moisture. Apply on surface the recommended primer. (**Life dur**, **Life dur water**). Dilute the product with water in a ratio of 5-15% and apply two coats.

VOC (VOLATILE ORGANIC COMPOUNDS)

EU limit value for this product (Category A/c "Coatings for exterior walls of mineral substrate", Type WB) is 40 g/l (2010). This product contains maximum 37 g/l VOC.



Coverage: 10-15m²/Lt



Drying: 1-2 hours



Dilution: 5-15% water



Packaging: 750ml, 3Lt, 10Lt



RESPONSIBLE DISPOSAL:
SAVAS CHALIAMPALIAS & CO
Tel.++30 2310 796663
Fax: ++30 2310 723147
IND.AREA OF THESSALONIKI
57022 SINDOS - GREECE

www.chromodomi.gr